



SAFETY DATA SHEET

Q 40-550 HIGH BUILD PRIMER FILLER White

Page: 1

Revision date: 17-01-2017

Revision No: 13

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Q 40-550 HIGH BUILD PRIMER FILLER White

Product code: Q 40-550-0503

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Firmenname: Q-Company Int. GmbH
Beckershof 3
24558 Henstedt-Ulzburg
Germany

Email: msds@qrefinish.com

1.4. Emergency telephone number

Emergency tel: +49 (0)551-19240 (Giftinformationszentrum-Nord)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; STOT SE 3: H336; -: H229; -: EUH066

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic to aquatic life with long lasting effects. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated
H411: Toxic to aquatic life with long lasting effects.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Danger

Hazard pictograms: GHS02: Flame

[cont...]

SAFETY DATA SHEET

Q 40-550 HIGH BUILD PRIMER FILLER White

Page: 2

GHS07: Exclamation mark

GHS09: Environmental



Precautionary statements: P501: Dispose of contents/container to an approved waste disposal according to local/regional/national/international regulations.

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251: Do not pierce or burn, even after use.

P211: Do not spray on an open flame or other ignition source.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P273: Avoid release to the environment.

P271: Use only outdoors or in a well-ventilated area.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P403: Store in a well-ventilated place.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIMETHYL ETHER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-065-8	115-10-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	37.500%

ETHYL METHYL KETONE

201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	15.000%
-----------	---------	---	--	---------

[cont...]

SAFETY DATA SHEET

Q 40-550 HIGH BUILD PRIMER FILLER White

Page: 3

ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	6.500%
-----------	---------	---	--	--------

N-BUTYL ACETATE

204-658-1	123-86-4	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	6.500%
-----------	----------	--	--	--------

TRIZINC BIS(ORTHOPHOSPHATE)

231-944-3	7779-90-0	-	Aquatic Chronic 1: H410; Aquatic Acute 1: H400	6.500%
-----------	-----------	---	--	--------

1-METHOXY-2-PROPANOL

203-539-1	107-98-2	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226; STOT SE 3: H336	6.500%
-----------	----------	--	-------------------------------------	--------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1.750%
-----------	-----------	---	---	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Generally the product does not irritate the skin.

Eye contact: Bathe the eye with running water for 15 minutes. If irritation persists, consult a doctor.

Ingestion: Do not induce vomiting. Call a doctor immediately.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. In case of complaints consult doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Generally the product does not irritate the skin.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

[cont...]

SAFETY DATA SHEET

Q 40-550 HIGH BUILD PRIMER FILLER White

Page: 4

to cool containers. Water fog. Dry chemical powder. Carbon dioxide. Alcohol resistant foam. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic charge in the immediate area. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

[cont...]

SAFETY DATA SHEET

Q 40-550 HIGH BUILD PRIMER FILLER White

Page: 5

8.1. Control parameters

Hazardous ingredients:

DIMETHYL ETHER

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	766 mg/m3	958 mg/m3	-	-

ETHYL METHYL KETONE

UK	600 mg/m3	899 mg/m3	-	-
----	-----------	-----------	---	---

ACETONE

UK	1210 mg/m3	3620 mg/m3	-	-
----	------------	------------	---	---

N-BUTYL ACETATE

UK	724 mg/m3	966 mg/m3	-	-
----	-----------	-----------	---	---

1-METHOXY-2-PROPANOL

UK	375 mg/m3	560 mg/m3	-	-
----	-----------	-----------	---	---

XYLENE

UK	220 mg/m3	441 mg/m3	-	-
----	-----------	-----------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter. Filter AX/P2

Hand protection: Nitrile gloves. Solvent-resistant gloves. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. The exact break through time has to be found out by the glove manufacturer; observed.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: White

Odour: Characteristic odour

Evaporation rate: Not applicable.

Solubility in water: Not / slightly miscible.

[cont...]

SAFETY DATA SHEET

Q 40-550 HIGH BUILD PRIMER FILLER White

Page: 6

Viscosity: No data available.

Boiling point/range°C: -24

Melting point/range°C: No data available.

Flammability limits %: lower: 1.1

upper: 20.0

Flash point°C: -42

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No autoignition

Vapour pressure: 4 Bar

Relative density: No data available.

pH: No data available.

VOC g/l: 684,5

9.2. Other information

Other information: Density: 0.923 g/cm³ (20°C) Ignition temperature: 235°C Solvent content: organic solvent: 70.7%. Solids content: 28.9%.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: No data available.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

[cont...]

SAFETY DATA SHEET

Q 40-550 HIGH BUILD PRIMER FILLER White

Page: 7

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

1-METHOXY-2-PROPANOL

IVN	RAT	LD50	4200	mg/kg
ORL	MUS	LD50	11700	mg/kg
ORL	RAT	LDLO	3739	mg/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Generally the product does not irritate the skin.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
Pimephales promelas	96H LC50	2993	mg/l
Daphnia magna	48H EC50	308	mg/l
CAS 78-93-3	-	-	-
CAS 67-64-1	-	-	-
Daphnia magna	EC50	8800	mg/l
Fish	96H	8300	mg/l

[cont...]

SAFETY DATA SHEET

Q 40-550 HIGH BUILD PRIMER FILLER White

Page: 8

CAS 7779-90-0	-	-	-
Ds	72H ErC50	0.14	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	0.14	mg/l

Hazardous ingredients:

ACETONE

BLUEGILL (<i>Lepomis macrochirus</i>)	LC50	8300	mg/l
---	------	------	------

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Waterbezwaarlijkheid (NL) 1: Zwarte lijst-stof (76/464/EEG).
Gevaar voor water klasse 1 (D) (Zelfclassificatie): gevaar voor water klein.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. Must not be disposed together with household garbage or into the sewage system.

Disposal of packaging: Uncleaned packagings: recommendation: Disposal according to official regulations.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

[cont...]

SAFETY DATA SHEET

Q 40-550 HIGH BUILD PRIMER FILLER White

Page: 9

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: Warning: Gases. EMS number:F-D,S-U.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No. 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.