

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

Article number: 50-200-0501

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Surface protection

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Q-Company Int. GmbH

Beckershof 3

24558 Henstedt-Ulzburg

web: www.qrefinish.com

Further information obtainable from: msds@qrefinish.com

1.4 Emergency telephone number: +49 (0)551-19240 (Giftinformationszentrum-Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 1)

· Hazard pictograms


GHS02 GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves / eye protection.

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures
· Description: Active substance with propellant

· Dangerous components:

CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas C, H280	25-<50%
EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	10-<25%

(Contd. on page 3)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 2)

CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone / MEK Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Naphtha (petroleum), hydrotreated light "(Note P; -R45, R46; <0,1% benzene)" Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	2.5-<10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black Self-heat. 1, H251	0.1-<1.0%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	0.1-<1.0%

· **Additional information:**

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 3)

- Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurised containers.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

74-98-6 propane

OEL	Short-term value: 3600 mg/m ³ , 2000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm
-----	---

78-93-3 butanone / MEK

WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
-----	---

1330-20-7 xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

(Contd. on page 5)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 4)

107-98-2 1-methoxy-2-propanol

WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
-----	---

1333-86-4 Carbon black

WEL	Short-term value: 7 mg/m ³ Long-term value: 3.5 mg/m ³
-----	---

64-17-5 ethanol

WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

· **DNELs****Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer) 773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m ³ (Consumer) 2035 mg/m ³ (Worker)

78-93-3 butanone / MEK

Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer) 1161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m ³ (Consumer) 600 mg/m ³ (Worker)

· **Ingredients with biological limit values:****78-93-3 butanone / MEK**

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

1330-20-7 xylene (mix)

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional Occupational Exposure Limit Values for possible hazards during processing:****100-41-4 ethylbenzene**

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

108-88-3 toluene

WEL	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
-----	--

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 6)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 5)

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· **Protection of hands:**



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol
Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: -44 °C

· **Flash point:** -97 °C

· **Flammability (solid, gas):** Not applicable.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 0.7 Vol %

Upper: 20.0 Vol %

(Contd. on page 7)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 6)

· Vapour pressure at 20 °C:	8300 hPa
· Density at 20 °C:	0.78 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	74.9 %
Solids content:	24.6 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2800 mg/kg (rabbit)
Inhalative	LC50/4 h	>23 mg/l (rat)

78-93-3 butanone / MEK

Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
		5000 mg/kg (rbt)

1330-20-7 xylene (mix)

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)

Naphtha (petroleum), hydrotreated light "(Note P; -R45, R46; <0,1% benzene)"

Oral	LD50	4300-6000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rabbit)
Inhalative	LC50/4h	>60 mg/l (rat)

(Contd. on page 8)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 7)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

NOELR (72h)	10 mg/l (Pseudokirchneriella subcapitata)
EL50 (72h)	10-30 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>13.4 mg/l (Oncorhynchus mykiss (96h))
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)
EC50/48h	3 mg/l (Daphnia magna)

78-93-3 butanone / MEK

LC50/96h	2993 mg/l (Pimephales promelas)
EC50/48h	308 mg/l (Daphnia magna)

1330-20-7 xylene (mix)

LC50/96h	8.9-16.4 mg/l (Pimephales promelas)
EC50/48h	3.2-9.5 mg/l (Daphnia magna)

Naphtha (petroleum), hydrotreated light "(Note P; -R45, R46; <0,1% benzene)"

LC50	35-37 mg/l (Fish)
------	-------------------

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· Ecotoxicological effects:

· **Remark:** Toxic for fish

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 9)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 8)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 02 99	wastes not otherwise specified
----------	--------------------------------

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, ADN, IMDG, IATA** UN1950

· **14.2 UN proper shipping name**

· **ADR, ADN** UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

· **IMDG** AEROSOLS (Naphtha (petroleum), hydrotreated light (Benzene < 0,1%), Naphtha (petroleum), hydrotreated light "(Note P; -R45, R46; <0,1% benzene)"), MARINE POLLUTANT

· **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.
 · **Label** 2.1

· **ADN**

· **ADN/R Class:** 2 5F

· **IMDG**



· **Class** 2.1
 · **Label** 2.1

· **IATA**



· **Class** 2.1
 · **Label** 2.1

(Contd. on page 10)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 9)

· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light (Benzene < 0,1%)
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

(Contd. on page 11)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 20.02.2017

Version: 18

Revision: 17.02.2017

Trade name: Q 50-200-0501 Stonechip Protection Spray -black-

(Contd. of page 10)

· **National regulations:**

Class	Share in %
NK	50-<75

- **VOC-CH** 74.85 %
- **VOC-EU** 585.4 g/l
- **Danish MAL Code** 5-3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H251 Self-heating; may catch fire.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Produktsicherheit
Research & Development

· **Contact:** Ing. J. Sleumer

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas C: Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Self-heat. 1: Self-heating substances and mixtures – Category 1
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered. ***