



## SAFETY DATA SHEET

Q 50-400 2K PU PLASTIC REPAIR - BLACK 30 SEC. (A)

Page: 1

Revision date: 26-1-2017

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** Q 50-400 2K PU PLASTIC REPAIR - BLACK 30 SEC. (A)

**Product code:** Q 50-400-3040

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants.

#### 1.3. Details of the supplier of the safety data sheet

**Firmenname:** Q-Company Int. GmbH  
Beckershof 3  
24558 Henstedt-Ulzburg  
Germany

**Email:** msds@qrefinish.com

#### 1.4. Emergency telephone number

**Emergency tel:** +49 (0)551-19240 (Giftinformationszentrum-Nord)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Eye Irrit. 2: H319; Acute Tox. 4: H332; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317

**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** \* H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Hazard pictograms:** GHS07: Exclamation mark

GHS08: Health hazard



[cont...]

# SAFETY DATA SHEET

Q 50-400 2K PU PLASTIC REPAIR - BLACK 30 SEC. (A)

Page: 2

**Signal words:** Danger

**Precautionary statements:** P501: Dispose of contents/container to.  
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P264: Wash hands thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P285: In case of inadequate ventilation wear respiratory protection.  
P302+352: IF ON SKIN: Wash with plenty of water/soap.  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+313: If skin irritation or rash occurs: Get medical advice/attention.  
P337+313: If eye irritation persists: Get medical advice/attention.  
P342+311: If experiencing respiratory symptoms: Call a physician.  
P362: Take off contaminated clothing.  
P403: Store in a well-ventilated place.  
P232: Protect from moisture.  
P233: Keep container tightly closed.

## 2.3. Other hazards

**Other hazards:** Danger of serious damage to health by prolonged exposure.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-966-0	101-68-8	-	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	50-70%

[cont...]

# SAFETY DATA SHEET

Q 50-400 2K PU PLASTIC REPAIR - BLACK 30 SEC. (A)

Page: 3

## METHYLENEDIPHENYL DIISOCYANATE

247-714-0	26447-40-5	-	Carc. 2: H351; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317; STOT SE 2: H371; STOT RE 2: H373	1-10%
-----------	------------	---	--	-------

### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Call a doctor immediately. Do not give any liquids. Do not induce vomiting.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. Provide oxygen if breathing is difficult. Give artificial respiration if not breathing and seek medical help immediately. Asthmatic - type symptoms may develop and may be immediate or delayed up to several hours.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

#### 4.3. Indication of any immediate medical attention and special treatment needed

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. Dry chemical powder. Carbon dioxide. Alcohol resistant foam. Water fog. Water is not recommended but may be applied in very large quantities as a fine spray when other extinguishing media are not available. Product reacts with water. Reaction may produce heat and/or gases.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

# SAFETY DATA SHEET

Q 50-400 2K PU PLASTIC REPAIR - BLACK 30 SEC. (A)

Page: 4

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. If outside keep bystanders upwind and away from danger point. Evacuate the area immediately. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Do not eat, drink or smoke when using this product. Workers should wash hands and face before eating, drinking and smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**DIPHENYLMETHANE-4,4'-DI-ISOCYANATE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

[cont...]

# SAFETY DATA SHEET

Q 50-400 2K PU PLASTIC REPAIR - BLACK 30 SEC. (A)

Page: 5

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves. Butyl gloves. Nitrile gloves. PVA gloves. However, please note that PVA degrades with water.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Beige

**Odour:** slightly musty odor

**Evaporation rate:** No data available.

**Boiling point/range°C:** 207,77

**Flash point°C:** >204,44

**Vapour pressure:** < 10-5 mm Hg @ 25°C

### 9.2. Other information

**Other information:** Vapor density: 8.5 (MDI) (Air = 1).

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions. Product is very unstable when contaminated with water.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Flames. Moisture. Avoid temperatures above 32°C. Avoid temperatures below 17°C.

### 10.5. Incompatible materials

**Materials to avoid:** Metals. Aluminium. Copper. Zinc. Acids. Alcohols. Amines. Bases. Strong oxidising agents. Water. Moist air. Ammonia. Metal compounds.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** Reaction with water can generate carbon dioxide. Polymerization can occur which could be catalyzed by strong bases and water.

[cont...]

# SAFETY DATA SHEET

Q 50-400 2K PU PLASTIC REPAIR - BLACK 30 SEC. (A)

Page: 6

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

ORL	MUS	LD50	2200	mg/kg
ORL	RAT	LD50	9200	mg/kg

**Relevant hazards for product:**

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** No data available.

[cont...]

# SAFETY DATA SHEET

Q 50-400 2K PU PLASTIC REPAIR - BLACK 30 SEC. (A)

Page: 7

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Regulation (EC) No. 1907/2006.  
This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335: May cause respiratory irritation.  
H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

