

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: professional use.

Application of the substance / the mixture Clear coating material, Varnish

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Q-Company Int. GmbH
Beckershof 3
24558 Henstedt-Ulzburg
web: www.qrefinish.com
phone: +49 (0)4193-75400

Further information obtainable from: msds@qrefinish.com

1.4 Emergency telephone number:

+49 (0)551-19240 (Giftinformationszentrum-Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 1)

Hazard pictograms

GHS02 GHS07

Signal word Warning**Hazard-determining components of labelling:**

isobutyl methacrylate

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

n-butyl acetate

heptan-2-one

Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 2)

Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-<20%
CAS: 110-43-0 EINECS: 203-767-1 Reg.nr.: 01-2119902391-49	heptan-2-one ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H336	2.5-10%
List no.: 918-668-5 Reg.nr.: 01-2119455851-35	hydrocarbons, C9, aromatics ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	2.5-10%
CAS: 108-10-1 EINECS: 203-550-1 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	1-7.5%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	0.1-1%
CAS: 75-65-0 EINECS: 200-889-7	2-methylpropan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	0.1-1%
List no.: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1A, H317	0.1-<1%
CAS: 97-86-9 EINECS: 202-613-0	isobutyl methacrylate ⚠ Flam. Liq. 3, H226; ⚠ Aquatic Acute 1, H400; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.1-<0.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	0.1-1%

(Contd. on page 4)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 3)

Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water.**After swallowing:** Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

(Contd. on page 5)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 4)

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents.

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage
--

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

(Contd. on page 6)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 5)

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****Additional information about design of technical facilities:**

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****123-86-4 n-butyl acetate**

WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
---------------------	---

110-43-0 heptan-2-one

WEL (Great Britain)	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk
---------------------	--

IOELV (EU)

Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 238 mg/m ³ , 50 ppm Skin
--

108-10-1 4-methylpentan-2-one

WEL (Great Britain)	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV
---------------------	--

IOELV (EU)

Short-term value: 208 mg/m ³ , 50 ppm Long-term value: 83 mg/m ³ , 20 ppm
--

67-64-1 acetone

WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
---------------------	--

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 6)

IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm
75-65-0 2-methylpropan-2-ol	
WEL (Great Britain)	Short-term value: 462 mg/m ³ , 150 ppm Long-term value: 308 mg/m ³ , 100 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin

Regulatory information WEL (Great Britain): EH40/2011

DNELs		
123-86-4 n-butyl acetate		
Dermal	DNEL	7 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	960 mg/m ³ (acute - systemic effects, workers) 960 mg/m ³ (acute - local effects, workers) 480 mg/m ³ (long-term - systemic effects, workers) 480 mg/m ³ (long-term - local effects, workers)
110-43-0 heptan-2-one		
Dermal	DNEL	54.27 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	1516 mg/m ³ (acute - systemic effects, workers) 394.25 mg/m ³ (long-term - systemic effects, workers)
hydrocarbons, C9, aromatics		
Dermal	DNEL	25 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	150 mg/m ³ (long-term - systemic effects, workers)
108-10-1 4-methylpentan-2-one		
Dermal	DNEL	11.8 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	208 mg/m ³ (acute - systemic effects, workers) 208 mg/m ³ (acute - local effects, workers) 83 mg/m ³ (long-term - systemic effects, workers) 83 mg/m ³ (long-term - local effects, workers)
67-64-1 acetone		
Dermal	DNEL	186 mg/kg bw/day (long-term - systemic effects, workers)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 7)

Inhalative	DNEL	2420 mg/m ³ (acute - local effects, workers) 1210 mg/m ³ (long-term - systemic effects, workers)
75-65-0 2-methylpropan-2-ol		
Dermal	DNEL	5.5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	214 mg/m ³ (acute - local effects, workers) 2.7 mg/m ³ (long-term - systemic effects, workers)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Dermal	DNEL	2.5 mg/kg bw/day (acute - systemic effects, workers) 2.5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	2.35 mg/m ³ (acute - systemic effects, workers) 2.35 mg/m ³ (long-term - systemic effects, workers)
97-86-9 isobutyl methacrylate		
Dermal	DNEL	5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	415.9 mg/m ³ (long-term - systemic effects, workers) 409 mg/m ³ (long-term - local effects, workers)
108-65-6 2-methoxy-1-methylethyl acetate		
Dermal	DNEL	153.5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	275 mg/m ³ (long-term - systemic effects, workers)
PNECs		
123-86-4 n-butyl acetate		
PNEC	0.18 mg/l (freshwater environment) 0.018 mg/l (marine environment) 0.36 mg/l (intermittent releases) 35.6 mg/l (sewage treatment plants)	
PNEC	0.981 mg/kg (freshwater sediment environment)	
110-43-0 heptan-2-one		
PNEC	0.0982 mg/l (freshwater environment) 0.00982 mg/l (marine environment) 0.982 mg/l (intermittent releases) 12.5 mg/l (sewage treatment plants)	
PNEC	1.89 mg/kg (freshwater sediment environment) 0.189 mg/kg (marine sediment environment) 0.321 mg/kg (soil)	

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 8)

108-10-1 4-methylpentan-2-one	
PNEC	0.6 mg/l (freshwater environment) 0.06 mg/l (marine environment) 1.5 mg/l (intermittent releases) 27.5 mg/l (sewage treatment plants)
PNEC	8.27 mg/kg (freshwater sediment environment) 0.83 mg/kg (marine sediment environment)
67-64-1 acetone	
PNEC	10.6 mg/l (freshwater environment) 1.06 mg/l (marine environment) 21 mg/l (intermittent releases) 100 mg/l (sewage treatment plants)
PNEC	30.4 mg/kg (freshwater sediment environment) 3.04 mg/kg (marine sediment environment) 29.5 mg/kg (soil)
75-65-0 2-methylpropan-2-ol	
PNEC	6.64 mg/l (freshwater environment) 0.664 mg/l (marine environment) 9.33 mg/l (intermittent releases) 690 mg/l (sewage treatment plants)
PNEC	5.8 mg/kg (freshwater sediment environment) 0.58 mg/kg (marine sediment environment) 1 mg/kg (soil)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
PNEC	0.0022 mg/l (freshwater environment) 0.00022 mg/l (marine environment) 0.009 mg/l (intermittent releases)
PNEC	1.05 mg/kg (freshwater sediment environment) 0.11 mg/kg (marine sediment environment) 0.21 mg/kg (soil)
97-86-9 isobutyl methacrylate	
PNEC	0.021 mg/l (freshwater environment) 0.0021 mg/l (marine environment)

(Contd. on page 10)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 9)

PNEC	0.2 mg/l (intermittent releases) 10 mg/l (sewage treatment plants) 5.89 mg/kg (freshwater sediment environment) 0.589 mg/kg (marine sediment environment) 1.16 mg/kg (soil)
108-65-6 2-methoxy-1-methylethyl acetate	
PNEC	0.635 mg/l (freshwater environment) 0.0635 mg/l (marine environment) 6.35 mg/l (intermittent releases) 100 mg/l (sewage treatment plants)
PNEC	3.29 mg/kg (freshwater sediment environment) 0.329 mg/kg (marine sediment environment)
Ingredients with biological limit values:	
108-10-1 4-methylpentan-2-one	
BMGV (Great Britain)	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one

Regulatory information BMGV (Great Britain): EH40/2011**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 10)

Protection of hands:



Protective gloves

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

PVA gloves

Recommended thickness of the material: $\geq 0,7$ mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 6 ≥ 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:

Fluid

Colour:

Colourless

Odour:

Characteristic

Odour threshold:

Not determined.

(Contd. on page 12)

**Safety data sheet**
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 11)

pH-value:	Not applicable.
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. 114 °C Undetermined.
Flash point:	>23 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits: Lower: Upper:	0.7 Vol % 15.0 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C: Vapour density Evaporation rate	0.98 g/cm ³ Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity**10.1 Reactivity** No decomposition if used according to specifications.**10.2 Chemical stability**

No decomposition if used and stored according to specifications.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 12)

10.3 Possibility of hazardous reactions

Reacts with alkali, amines and strong acids.

Reacts with oxidising agents.

Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid Protect from heat and direct sunlight.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information
--

11.1 Information on toxicological effects**Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****123-86-4 n-butyl acetate**

Oral	LD50	10760 mg/kg (rat)
Dermal	LD50	10760 mg/kg (rat)
		>14000 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)

110-43-0 heptan-2-one

Oral	LD50	1600 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	> 16.7 mg/l (rat)

hydrocarbons, C9, aromatics

Oral	LD50	3592 mg/kg (rat)
Dermal	LD50	>3160 mg/kg
Inhalative	LC50/4 h	> 6193 mg/l (rat)

108-10-1 4-methylpentan-2-one

Oral	LD50	2080 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	10-20 mg/l (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	7400 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 13)

75-65-0 2-methylpropan-2-ol		
Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Oral	LD50	3230 mg/kg (rat)
Dermal	LD50	>3170 mg/kg (rat)
97-86-9 isobutyl methacrylate		
Oral	LD50	11990 mg/kg (mouse)
Dermal	LD50	17760 mg/kg 17760 mg/kg (guinea pig)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/6 h	4345 mg/l (rat)

Primary irritant effect:**Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.**Reproductive toxicity**

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 15)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 14)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

123-86-4 n-butyl acetate

LC50/96 h	18 mg/l (Pimephales promelas)
TT/16 h	115 mg/l (Pseudomonas putida)
EC50/48 h	44 mg/l (daphnia)
EC50/72 h	675 mg/l (algae)

110-43-0 heptan-2-one

LC50/96 h	131 mg/l (Pimephales promelas)
EC50/72 h	98.2 mg/l (Pseudokirchnerella subcapitata)

hydrocarbons, C9, aromatics

ErC50/96 h	9.2 mg/l (fish)
EL50/48 h	3.2 mg/l (Daphnia magna)
ErL50/72 h	2.9 mg/l (Pseudokirchnerella subcapitata)
EC50/48 h	6.14 mg/l (Daphnia magna)
EC50/10 min	>99 mg/l (microorganisms)

67-64-1 acetone

LC50/96 h	5540 mg/l (oncorhynchus mykiss)
EC50/24 h	(marine sediment environment)
LC50/48 h	8800 mg/l (Daphnia pulex)

75-65-0 2-methylpropan-2-ol

LC50/96 h	>961 mg/l (Pimephales promelas)
EC50/48 h	933 mg/l (Daphnia magna)
EC50/24 h	>976 mg/l (Pseudokirchnerella subcapitata)
EC50/16 h	>10 g/l (Pseudomonas putida)

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

LC50/96 h	0.97 mg/l (fish)
EC50/3 h	>100 mg/l (microorganisms)
EC50/72 h	1.68 mg/l (Desmodesmus subspicatus)
EC50/24 h	20 mg/l (Daphnia magna)

(Contd. on page 16)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 15)

97-86-9 isobutyl methacrylate	
LC50/96 h	20 mg/l (fish)
EC50/48 h	210 mg/l (invertebrates)
ECO/16 h	>281 mg/l (<i>Pseudomonas fluorescens</i>)
EC50/72 h	44 mg/l (<i>Pseudokirchnerella subcapitata</i>)
108-65-6 2-methoxy-1-methylethyl acetate	
LC50/96 h	>100 mg/l (fish)
EC50/48 h	>500 mg/l (<i>Daphnia magna</i>)
EC20/30 min	>1000 mg/l (microorganisms)
EC50/72 h	>1000 mg/l (<i>Pseudokirchnerella subcapitata</i>)
EC50	>100 mg/l (<i>Pseudokirchnerella subcapitata</i>) >100 mg/l (<i>Pimephales promelas</i>) >100 mg/l (<i>Daphnia magna</i>)
12.2 Persistence and degradability	
123-86-4 n-butyl acetate	
Biodegradation	83 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)
110-43-0 heptan-2-one	
Biodegradation	69 % (readily biodegradable) (OECD 310, 28 d, aerobic)
hydrocarbons, C9, aromatics	
Biodegradation	78 % (readily biodegradable) (OECD 301 F, 28 d, aerobic)
67-64-1 acetone	
Biodegradation	90.9 % (readily biodegradable) (OECD 301B, 28d, aerobic)
75-65-0 2-methylpropan-2-ol	
Biodegradation	(readily biodegradable)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Biodegradation	38 % (not readily biodegradable) (OECD 301 F, 28 d, aerobic)
97-86-9 isobutyl methacrylate	
Biodegradation	74.3 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)
108-65-6 2-methoxy-1-methylethyl acetate	
Biodegradation	100 % (readily biodegradable) (OECD 302 B, 8 d, aerobic)
12.3 Bioaccumulative potential	
123-86-4 n-butyl acetate	
BCF	15.3 (-)

(Contd. on page 17)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 16)

log Pow	2.3
67-64-1 acetone	
BCF	3 (-)
log Pow	-0.24
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
BCF	<9.7
97-86-9 isobutyl methacrylate	
BCF	61.9
108-65-6 2-methoxy-1-methylethyl acetate	
log Pow	0.56
12.4 Mobility in soil	
123-86-4 n-butyl acetate	
log Koc	1.27
67-64-1 acetone	
Kd	1.5 l/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
log Koc	5.31
Koc	204400
97-86-9 isobutyl methacrylate	
log Koc	2.47
Koc	2767
108-65-6 2-methoxy-1-methylethyl acetate	
Koc	1.7

Additional ecological information:**General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.

(Contd. on page 18)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 17)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

1263 PAINT

IMDG, IATA

PAINT

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class

3

Label

3

14.4 Packing group

ADR, IMDG, IATA

III

14.5 Environmental hazards:

Marine pollutant (IMDG):

No

14.6 Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler):

30

EMS Number:

F-E,S-E

(Contd. on page 19)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 18)

Stowage Category	A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	

ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E

IMDG	
Limited quantities (LQ)	5L
UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category P5c** FLAMMABLE LIQUIDS**Qualifying quantity (tonnes) for the application of lower-tier requirements**

5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements

50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20**National regulations:****Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

(Contd. on page 20)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 19)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Sensitisation - Skin. Hazard Category 1
Skin Sens. 1A: Sensitisation - Skin. Hazard Category 1A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. on page 21)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2017

V- 1

Revision: 01.06.2016

Trade name: Q 70-265 2K UHS Clearcoat VOC 2:1

(Contd. of page 20)

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources European Chemicals Agency, <http://echa.europa.eu/>

— EN —