



Printing date 18.05.2017 Revision: 18.05.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Q 70-420 RALLYE SPRAY matt
- · Article number (product ID.): Q 70-420
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Q-Company Int. GmbH

Beckershof 3

24558 Henstedt-Ulzburg

E-mail: msds@qrefinish.com

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:
- · +49 (0)551-19240 (Giftinformationszentrum-Nord)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319

Causes serious eye irritation.

STOT SE 3 H336

May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

ace to ne

n-butyl acetate

(Contd. on page 2)

Printing date 18.05.2017 Revision: 18.05.2017

Trade name: Q 70-420 RALLYE SPRAY matt

(Contd. of page 1)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P261 Avoid breathing vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information: Without adequate ventilation, explosive atmosphere/gas mix may be created.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| Dangerous components: | | |
|---|--|---------|
| CAS: 67-64-1 | acetone | 25-<50% |
| EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx | ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336 | |
| CAS: 106-97-8 | butane (containing $\leq 0.1 \%$ butadiene (203-450-8)) | 10-<25% |
| EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx | 🍅 Flam. Gas 1, H220; 🔷 Press. Gas C, H280 | |
| CAS: 115-10-6 | dimethyl ether | 10-<25% |
| EINECS: 204-065-8 | 🏇 Flam. Gas 1, H220; 🔷 Press. Gas C, H280 | |
| Reg.nr.: 01-2119472128-37-xxxx | | |
| CAS: 74-98-6 | propane | 10-<25% |
| EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx | 🕸 Flam. Gas 1, H220; 🔷 Press. Gas C, H280 | |
| CAS: 123-86-4 | n-butyl acetate | 5-<10% |
| EINECS: 204-658-1 | 🏵 Flam. Liq. 3, H226; 🕠 STOT SE 3, H336 | |
| Reg.nr.: 01-2119485493-29-xxxx | • | |
| CAS: 1330-20-7 | xylene, mixture of isomers | 5-<10% |
| Reg.nr.: 01-2119486136-34-xxxx | Flam. Liq. 3, H226; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315 | |

Printing date 18.05.2017 Revision: 18.05.2017

Trade name: Q 70-420 RALLYE SPRAY matt

| | (Co | ontd. of page 2 |
|--------------------------------|---|-----------------|
| CAS: 108-65-6 | 2-methoxy-1-methylethyl acetate | 2.5-<5% |
| EINECS: 203-603-9 | ♦ Flam. Liq. 3, H226 | |
| Reg.nr.: 01-2119475791-29-xxxx | • | |
| CAS: 108-10-1 | 4-methylpentan-2-one | 1-<2.5% |
| EINECS: 203-550-1 | b Flam. Liq. 2, H225; b Acute Tox. 4, H332; Eye Irrit. 2, | |
| Reg.nr.: 01-2119473980-30-xxxx | H319; STOT SÉ 3, H335 | |
| CAS: 9004-70-0 | Nitrocellulose | 1-<2.5% |
| | ♦ Flam. Sol. 1, H228 | |
| CAS: 64-17-5 | ethanol | 1-<2.5% |
| EINECS: 200-578-6 | 🚸 Flam. Liq. 2, H225; 🕚 Eye Irrit. 2, H319 | |
| Reg.nr.: 01-211945761043-xxxx | | |

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB

Printing date 18.05.2017 Revision: 18.05.2017

Trade name: Q 70-420 RALLYE SPRAY matt

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

| edients with limit values that require monitoring at the workplace: |
|---|
| 4-1 acetone |
| Short-term value: 3620 mg/m³, 1500 ppm |
| Long-term value: 1210 mg/m³, 500 ppm |
| 97-8 butane (containing ≤0,1 % butadiene (203-450-8)) |
| Short-term value: 1810 mg/m³, 750 ppm |
| Long-term value: 1450 mg/m³, 600 ppm |
| Carc (if more than 0.1% of buta-1.3-diene) |
| 10-6 dimethyl ether |
| Short-term value: 958 mg/m³, 500 ppm |
| Long-term value: 766 mg/m³, 400 ppm |
| 86-4 n-butyl acetate |
| Short-term value: 966 mg/m³, 200 ppm |
| Long-term value: 724 mg/m³, 150 ppm |
| -20-7 xylene, mixture of isomers |
| Short-term value: 441 mg/m³, 100 ppm |
| Long-term value: 220 mg/m³, 50 ppm |
| Sk; BMGV |
| 65-6 2-methoxy-1-methylethyl acetate |
| Short-term value: 548 mg/m³, 100 ppm |
| Long-term value: 274 mg/m³, 50 ppm |
| Sk |
| |

(Contd. on page 5)

Printing date 18.05.2017 Revision: 18.05.2017

Trade name: Q 70-420 RALLYE SPRAY matt

(Contd. of page 4)

108-10-1 4-methylpentan-2-one

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

Sk, BMGV

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

· Ingredients with biological limit values:

1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift
Parameter: methyl hippuric acid

108-10-1 4-methylpentan-2-one

BMGV 20 µmol/L

Medium: urine

Sampling time: post shift

Parameter: 4-methylpentan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

 $butyl\ rubber,\ 0,7mm$

· Eye protection:



Tightly sealed goggles

Printing date 18.05.2017 Revision: 18.05.2017

Trade name: Q 70-420 RALLYE SPRAY matt

(Contd. of page 5)

| 0.1 Information on basis should at a 1 | howing I was out as |
|--|--|
| 9.1 Information on basic physical and c General Information | nemicai properties |
| Appearance: | |
| Form: | Aerosol |
| Colour: | Different colour shades |
| Odour: | Solvent-like |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range | : -44 °C |
| Flash point: | -97 °C |
| | Without propellant gas. |
| Flammability (solid, gas): | Not applicable. |
| Ignition temperature: | 235 °C |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | In use, may form flammable/explosive vapour-air mixture. |
| Explosion limits: | |
| Lower: | 1.5 Vol % |
| Upper: | 18.6 Vol % |
| Vapour pressure at 20 °C: | 3600 hPa |
| Density: | Not determined. |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not applicable. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| Solvent content: | |
| Organic solvents: | 91.0 % |
| VOC (EU) | With propellant gas. Content given by weight. 90.98 % |
| Solids content: | 9.0 % |
| 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.

(Contd. on page 7)

Printing date 18.05.2017 Revision: 18.05.2017

Trade name: Q 70-420 RALLYE SPRAY matt

(Contd. of page 6)

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Possible in traces.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GB

Printing date 18.05.2017 Revision: 18.05.2017

Trade name: Q 70-420 RALLYE SPRAY matt

(Contd. of page 7)

| SECTION 14: Transport informat | |
|---|--|
| 14.1 UN-Number | |
| ADR, IMDG, IATA | UN1950 |
| 14.2 UN proper shipping name | |
| ADR | 1950 AEROSOLS |
| IMDG | AEROSOLS |
| IATA | AEROSOLS, flammable |
| 14.3 Transport hazard class(es) | |
| ADR | |
| 2 | |
| Class | 2 5F Gases. |
| Label | 2.1 |
| IMDG, IATA | |
| | |
| Class | 2.1 |
| Label | 2.1 |
| 14.4 Packing group | |
| ADR, IMDG, IATA | Void |
| , , | not classified |
| 14.5 Environmental hazards: | |
| Marine pollutant: | No |
| 14.6 Special precautions for user | Warning: Gases. |
| Danger code (Kemler): | - |
| | not classified |
| EMS Number: | F- D , S - U |
| Stowage Code | SW1 Protected from sources of heat. |
| | SW22 For AEROSOLS with a maximum capacity of 1 lit |
| | Category A. For AEROSOLS with a capacity above 1 lit |
| | Category B. For WASTE AEROSOLS: Category C, Cle |
| | of living quarters. |
| Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 lit |
| | Segregation as for class 9. Stow "separated from" class |
| | except for division 1.4. For AEROSOLS with a capac |
| | above 1 litre: Segregation as for the appropric subdivision of class 2. For WASTE AEROSOL |
| | Segregation as for the appropriate subdivision of class 2. |
| 14.7 Transport in bulk according to Anno Marpol and the IBC Code | |
| Transport/Additional information: | 11 |
| 5 | |
| ADR | IL |
| Limited quantities (LQ) Excepted quantities (EQ) | TL Code: E0 |
| Excepted quantities (EQ) | |
| | Not permitted as Excepted Quantity |

Printing date 18.05.2017 Revision: 18.05.2017

Trade name: Q 70-420 RALLYE SPRAY matt

| | (Contd. of page 8 |
|--|------------------------------------|
| · Transport category | 2 |
| Tunnel restriction code | D |
| ·IMDG | |
| · Limited quantities (LQ) | IL |
| \cdot Excepted quantities (\widetilde{EQ}) | Code: E0 |
| | Not permitted as Excepted Quantity |
| · UN ''Model Regulation'': | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

| Class | Share in % |
|-------|------------|
| NK | 50-100 |

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Printing date 18.05.2017 Revision: 18.05.2017

Trade name: Q 70-420 RALLYE SPRAY matt

(Contd. of page 9)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Flam. Sol. 1: Flammable solids – Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.