



Technical Data Sheet

Q 10-180 Striping Tape


Characteristics:

Q 10-180 Striping Tape uses a thermally stabilised polypropylene backing with a urethane based pressure sensitive adhesive. The product performs in temperatures up to 138°C for at least 45 minutes - leaving a sharp, clean separation line. The product is pre-cut into 8 sections across the roll making it ideal for striping coach lines in a multitude of configurations. The Q 10-180 is easy to use and saves time and money during the pin striping process.


Technical Data:

Values shown are typical values and not to be used for specification purposes.

Carrier	Embossed Polypropylene
Colour	Olive Green
Adhesive	Pigmented Urethane Pressure Sensitive Adhesive
Thickness	0.127mm PSTC-33
Width	25mm (+/- 1mm)
Length	14m (+/- 0.1m)
Tensile Strength	0.215 kg/mm ASTM D-3759
Elongation at Break	600%
Adhesion to Steel	33.6 g/mm ASTM D-3330
Heat Resistance	138°C Maximum for 45 minutes



Shelf life



Store in
dry and cool place

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.

Copyright: Q-Company 2017, all rights reserved.

Q-Company Int. GmbH / Beckershof 3 / D-24558 Henstedt-Ulzburg / Germany

Version: 02.01.2017