



# Technical Datasheet

## Q 20-010 Easyfill Putty

### Characteristics:

Multi-purpose fill putty characterized by creamy consistency. It contains fine-grained fillers. This putty is very easy to apply in both thin and thick layers. It creates a smooth, elastic and soft to sand coating. Adhesion to steel and polyester surfaces.

### Application:

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2-3% of BPO hardener. Apply within 3 - 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

Note:

Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply over wash primers and one component acrylic products.

### Technical data:

Density: 1,91 - 1,92 g/cm<sup>3</sup>


Color: beige



2004/42/II(b)(250)<250




Cleaning  
60-010



BPO- 2-3%




Pot life  
3- 5 min 20°C




20 - 30 min 20°C




Hand sanding / dry:  
P100 - P320



Machine sanding / dry:  
P100 - P320



Shelf life:  
12 Month



Store in cool place



Latex / Nitril

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.

Copyright: Q-Company 2017, all rights reserved.

Q-Company Int. GmbH / Beckershof 3 / D-24558 Henstedt-Ulzburg / Germany

Version: 02.01.2017