



Technical Data Sheet

Q 40-050 1K Acrylic Filler grey

Charakteristics:

40-050 is a 1K air-drying acrylic filler with good filling power and good adhesion to sanded old paints, sheet metal, aluminum and galvanized zinc. Ideal for new parts or smaller surfaces. Contains active rust protection pigments.

Application


The substrate must be clean, dry and free of grease, as well as matted or sanded. Dilute 40-050 to the desired spray viscosity, max. 50%. 1-2 layers, 30-45 my.

Technical Data:


Density: 1,78 g/cm³




grey



Filler100
1K thinner50



N/A




15-18 sek. 20°C
F4 cup




Clean
60-010/60-011



1,3 - 1,8mm




1-2




3-5 min 20°C



20-25 min



5-10 min




no



dry P320-500
wet P600-1200



dry P320-500



store at a dry
and cool place



2004/42/IIIB(c)(540)<540

Dieses Datenblatt dient nur zu Informationszwecken. Nach unserem Kenntnisstand entsprechen die angegebenen Daten dem neuesten Standard und beruhen auf jahrelanger Erfahrung in der Herstellung unserer Produkte.
Copyright: Q-Company 2019, alle Rechte vorbehalten

Q-Company Int. GmbH / Beckershof 3 / D-24558 Henstedt-Ulzburg / Germany
Version: 02.01.2017